



LANDFILL PRODUCT DATA SHEET

PNEUMATIC FOAM UNIT 2500/60



A self-propelled foam generating system engineered and configured to apply daily cover on larger landfills with working faces greater than 10,000ft². Exceptionally durable and reliable all-weather design uses easy to replace modular components to maximize your uptime. Climate controlled cab provides superb operator safety and turns the task of daily cover into a quick, one-person operation. Foam is applied using our patented bi-directional manifold.

The unit includes diesel driven hydraulics, air compressor, Caterpillar® tracks and drive assemblies, pump, hoses, solution storage tank, freeze protection and proprietary foam generating technology.

FEATURES

- Caterpillar diesel power
- Requires one person to operate
- Reliable Caterpillar undercarriage
- Equipped with freeze protection system
- Foam applied via manifold
- No clean up required
- Durable, rugged construction
- Hydrostatic drive

SPECIFICATIONS

Solution Storage Tank.....2,500 Gallons
Coverage Rate.....400 – 800 Sq. Ft./Min.
Coverage Area per fill..... 14,000 – 28,000 Sq. Ft.
Size..... 19'7" L x 10'2" W x 11'7" H
Dry Weight..... 40,000 Pounds
Products..... Soil Equivalent Foam or AC-900 Series