



REMEDIATION PRODUCT DATA SHEET

PNEUMATIC FOAM UNIT 2500/60



A self-propelled foam generating system designed and configured specifically for the largest remediation applications. Ideal for sites where covering large areas quickly is a top priority. Completely self-contained and designed to meet the demands of remediation applications where equipment is often left exposed to the elements. Foam is applied using our patented bi-directional manifold or optional hose reel(s) can be added depending upon your needs.

The unit includes diesel driven hydraulics, air compressor, Caterpillar® tracks and drive assemblies, pump, hoses, solution storage tank, freeze protection and proprietary foam generating technology.

FEATURES

- Caterpillar diesel power
- Requires one person to operate
- Reliable Caterpillar undercarriage
- Equipped with freeze protection system
- Foam applied via manifold
- No clean up required
- Durable, rugged construction
- Hydrostatic drive

SPECIFICATIONS

Solution Storage Tank.....	2,500 Gallons
Coverage Rate.....	400 – 800 Sq. Ft./Min.
Coverage Area per fill.....	28,000 – 35,000 Sq. Ft.
Size.....	19'7" L x 10'2" W x 11'7" H
Dry Weight.....	40,000 Pounds
Products.....	All Long Duration and Soil Equivalent Foam Products